



Miller Maxstar 200 Professional TIG Outfit (PTO)

Order # PTOMM200-26F12



Order your TIG—PTO today!

This PTO includes:

- TL26 FX torch body, 200 AMP, Gas Cooled, Flex Head (Trim-Line Torches are CK Exclusive)
- 12.5 foot SuperFlex Cable
- ½" Dinse - Installed
- Wheeled Remote Amperage Control—14 pin
- 10 foot Leather Velcro Hose Cover
- 6 foot Inert Argon Hose
- Flowmeter/Regulator* (CGA580)
- Accessory Kit—with cups, 1/16," 3/32" & 1/8" collets, collet bodies, tungsten, and backcap
- 12.5 foot Ground Clamp

**MASTER
TIG**
The choice
of master
Craftsmen

**Available without Regulator see reverse for part number and individual part numbers.*

CK Worldwide, Inc.

PO Box 1636, Auburn, WA 98071 USA
Phone: 1.800.426.0877 Fax: 1.800.327.5038
FORM 436 Nov/2011

www.CKWORLDWIDE.com

© 2011 CK Worldwide, Inc.

Follow Us:





Individual Part Numbers for the PTOMM200-26F12:

Description	Order Number
Gas Cooled Torch body, 200 AMP, Flex Head without Valve (3 series)	TL26 FX
Gas Cooled Torch body, 200 AMP, Rigid Head without Valve (3 series)	TL26 RG
12.5' SuperFlex 1 piece Power Cable	46V28RSF
25' SuperFlex 1 piece Power Cable	46V30RSF
½" Dinse connector (with Special 12" Argon Hose)*	SL8-35-12IN
15' Wheeled Remote Amperage Control—14 Pin**	WACCV-1-1-M14
28' Wheeled Remote Amperage Control—14 Pin**	WACCV-1-2-M14
10' Leather Velcro Hose Cover	212HCLV
22' Leather Velcro Hose Cover	225HCLV
Accessory Kit—with cups, 1/16", 3/32" & 1/8" collets, collet bodies, tungsten and short backcap.	AK-3
6' Inert Argon Hose	ARH-6
Flowmeter/Regulator (CGA580)	191AR-60
12.5' Ground Clamp	GC-200-12

*SL8-35-12IN, Required to use with Miller Maxstar 200, not included with the torch packages listed below.

** Linear slide or Rotary dial versions also available upon request.



Replacement Torch Packages for the PTOMM200-26F12:

Description	Order Number
12.5' Gas Cooled Torch Package, 200 AMP, Flex Head without Valve and 1 Piece SuperFlex Cable	TL26-12-RSF FX
12.5' Gas Cooled Torch Package, 200 AMP, Rigid Head without Valve and 1 Piece SuperFlex Cable	TL26-12-RSF RG
25' Gas Cooled Torch Package, 200 AMP, Flex Head without Valve and 1 Piece SuperFlex Cable	TL26-25-RSF FX
25' Gas Cooled Torch Package, 200 AMP, Rigid Head without Valve and 1 Piece SuperFlex Cable	TL26-25-RSF RG

PTO without Regulator:

Description	Order Number
TL26 FX, 46V28RSF, SL8-35-12IN, WACCV-1-1-M14, 212HCLV, AK-3, ARH-6 and GC-200-12	PTOMM20026F12NR

CK Worldwide, Inc.
 PO Box 1636, Auburn, WA 98071 USA
 Phone: 1.800.426.0877 Fax: 1.800.327.5038

www.CKWORLDWIDE.com

© 2011 CK Worldwide, Inc.

Follow Us:

